






<p>Good suction/self-priming, 60psi pressure. Can handle some suspended solids Good for viscous fluids (gels, paste, sauce etc.) Low shear, no foaming, gentle on your product – very little product damage is one of the main advantages of this type of pump. Wide range of chemical tolerant stators Food grade materials Welded triclamp fittings (no threads) Variable frequency drive enables wide range of voltage options and variable pumping speeds as well as higher rpm. Special variable gear box (variator) option available for very low speed e.g. dosing.</p>	<p>PH19 4 GPM/ 1 inch 0.33HP <i>Good for filtering</i> <i>Low flow rates</i> <i>Metering/Dosing</i></p>	<p>PH30 16 GPM/ 1.5 inch 0.75HP <i>Good work horse</i> <i>general purpose</i></p>	<p>PH35 23 GPM/ 2 inch 2HP <i>More powerful motor, 2" fittings</i></p>
 <p>Just the motor and pump. Fixed speed 3 phase or 240V single phase</p>	<p>\$711</p>	<p>\$1221</p>	<p>\$1713</p>
 <p>Add Cart</p>	<p>\$520</p>	<p>\$520</p>	<p>\$520</p>
 <p>Add a NEMA 4X variable speed drive with isolator switch 120V or 240V single phase Or 3 phase options</p>	<p>\$385</p>	<p>\$385</p>	<p>\$474</p>
 <p>Add an electric fan if the pump is to be operated for long periods at slow speeds. Fitted onto the rear of the motor.</p>	<p>\$260</p>	<p>\$260</p>	<p>\$360</p>
 <p>Complete pump on cart with variable speed drive.</p>	<p>No cooling fan: \$1,616 With cooling fan: \$1,876</p>	<p>No cooling fan: \$2,126 With cooling fan: \$2,386</p>	<p>No cooling fan: \$2,707 With cooling fan: \$3,067</p>